


HL63193MG (preliminary)


AlGaInP Laser Diode

638nm/700mW

Outline



Internal Circuit



Features:

- Shorter wavelength: 638nm Typ.
- High optical output power: 700mW
- Small package: $\phi 5.6$ mm
- Multi transverse mode
- TM mode oscillation

Applications:

- Laser projector
- Show Laser
- Light source of optical equipment

(Note1) This product is under development. Therefore, the specification is changed without notice

Absolute Maximum Ratings (T_c=25°C)

Item	Symbol	Ratings	Unit
Optical output power(1) (-10 to +30 °C)	P _o (1)	700	mW
Optical output power(2) (+30 to +40 °C)	P _o (2)	550	mW
LD Reverse Voltage	V _{R(LD)}	2	V
Operating Temperature	T _{opr}	-10 ~ +40	°C
Storage Temperature	T _{stg}	-40 ~ +85	°C

Operating temperature “T_{opr}” is defined by Case temperature “T_c”. High increase in temperature of LD chip itself is expected during operation due to high current density and small package.

Thus, without proper heat dissipation, it is observed that no specific output power is achieved or it results to LD degradation. It is advised that sufficient measure of heat dissipation should be taken so that LD's maximum operating temperature is not exceeded during actual operation.

Optical and Electrical Characteristics (T_c=25°C)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Threshold current	I _{th}	-	200	250	mA	-
Operating current	I _{op}	-	900	1100	mA	P _o =700mW
Operating voltage	V _{op}	-	2.3	2.8	V	P _o =700mW
Beam divergence Parallel to the junction	θ _{//}	-	8	20	°	P _o =700mW, FWHM
Beam divergence Perpendicular to the junction	θ _⊥	20	35	50	°	P _o =700mW, FWHM
Lasing Wavelength	λ _p	632	638	643	nm	P _o =700mW

Cautions

- 1.Oclaro Japan,Inc.(OCJ) neither warrants nor grants licenses of any our lights or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document, OCJ bears no responsibility for problems that may arise with third party's right, including intellectual property rights, in connection with use of the information contained in this document.
- 2.Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
- 3.OCJ makes every attempt to ensure that its products are of high quality and reliability. However, contact our sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic safety equipment or medical equipment for life support.
- 4.Design your application so that the products is used within the ranges guaranteed by OCJ. particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. OCJ. bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating OCJ product does not cause bodily injury, fire or other consequential damage due to operation of the OCJ product.
- 5.This product is not designed to be radiation resistant.
- 6.No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from OCJ.
- 7.Contact our sales office for any questions regarding this document or OCJ. products.

- 1.The laser light is harmful to human body especially to eye no matter what directly or indirectly. The laser beam shall be observed or adjusted through infrared camera or equivalent.
- 2.This product (without violet laser diode) contains gallium arsenide (GaAs), which may seriously endanger your health even at very low doses. Please avoid treatment which may create GaAs powder or gas, such as disassembly or performing chemical experiments, when you handle the product. When disposing of the product, please follow the laws of your country and separate it from other waste such as industrial waste and household garbage.

Contact Information

www.oclaro.com

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by Oclaro before they become applicable to any particular order or contract. In accordance with the Oclaro policy of continuous improvement specifications may change without notice. Further details are available from any Oclaro sales representative.



Caution - use of controls or adjustments or performance of procedures other than those specified herein may result in hazardous radiation exposure.

D00xxx-PB Issue nn Month Year
©Oclaro 2013. Oclaro, the Oclaro, Inc. logo, and all other Oclaro, Inc. product names and slogans are trademarks or registered trademarks of Oclaro, Inc. in the U.S.A. or other countries. Products described in this datasheet may be covered by one or more patents in the U.S.A. and abroad. Information in this datasheet is subject to change without notice.